## Ibigawa Bridge

A huge extradosed bridge of hybrid steel and concrete segment construction.



Client : Japan Highway Public Corporation **Project Site** : Kuwana City, Mie Prefecture

**Completion Year** : 2001 : 1397m Bridge Type

**Construction Structure** : 6 Span Continuous Extradosed Box Girder Bridge of Integrated PC and Steel

Structure

Width : 33m

Span Length : 271.5m (Steel girder section consists of 100m and 95m) Main Tower Length : 30m from the bridge deck (Number of stay cables 12) : Cantilever Erection Method Through Erection Noses **Construction Method** 

Manufacturing Method : Short Line Match Cast Method

Main Girder Cross Section : Tri Chambered Box Girder (With Upper Slab Rib Attached) Award

: Japan Society of Civil Engineers Tanaka Award 2001


Japan Prestressed Concrete Institute Award for Work 2001

References : Bridge and Foundation Engineering January 2001 Issue and Journal of


Prestressed Concrete No.2 1999

The above bridge construction method is identical to the adjacent Kisogawa Bridge and was constructed simultaneously. The segments were transported through a pontoon bridge located at the mouth of the Ibi and Kiso rivers. Both Ibigawa Bridge and Kisogawa Bridge had the same production site and equipment for the segment. It has a high damping rubber with two bearing lines installed on top of the piers. Since the span was substantial, the amount of deformation was considerably noticeable, causing the work execution extremely challenging due to immediate deformation during stock duration. The central steel girder was carried through a pontoon and lifted up by attaching the connector to the tip of the concrete girder integrated with the steel girder. Stay cables for the main tower is a tension-type and was affixed by using steel shelled cells. The tensioning for the stay cables was applied from the main girder side. Incidentally, the main tower was designed to resemble the sails of a yacht, and the concrete section was constructed after the tensioning of the stay cables.

## Side View




## Cross Section View





Segment Manufacturing Yard





Erection Equipment for Segments



Completion of the Segment Installation



Harumi Center Bldg. 3F, 2-5-24, Harumi, Chuo-ku, Tokyo 104-8215 TEL. +81-3-6385-8060